

UNPARALLELED CUSTOM PROTECTION




GUARDIAN™ SERIES



GUARDIAN by ZERO

CUSTOMIZED PROTECTION FOR YOUR SPECIFIC CONTENTS

ZERO KNOWS that extraordinary needs demand unique capabilities. We also realize that your equipment is invaluable and requires protection that may not be an off-the-shelf solution. Using GUARDIAN cases, our protection experts can design and build custom internal hardware-mounting and foam configuration options that offer the highest degree of protection possible for your specific contents and applications.




EQUIPMENT MOUNTING AND CUSTOMIZED FOAM OPTIONS AS LIMITLESS AS YOUR APPLICATIONS REQUIRE

GUARDIAN cases have pre-molded slots, for optional metal or plastic brackets which support either an optional Panel Ring or a direct connection to a custom panel allowing for nearly any configuration possible.

No drilling is required and panels are only affixed using screws attached to the mounting brackets, the cases remain waterproof without any compromise to strength.

OPTIONS



Custom Foam



Plastic Clips



Metal Clips



Panel Ring



Equipment Panels

UNPARALLELED CUSTOMIZED PROTECTION



GUARDIAN by ZERO

The **GUARDIAN** line offers the highest durability in an external case with the specific yet flexible protection inside that individual applications demand.

- Made of Copolymer Polypropylene Compound
- Chemical Resistant

GUARDIAN cases are tested and certified to the following standards:

- IP67 Waterproof, Dust-proof
- Defence Standard 81-41 Level J
- STANAG 4280 (edition 2)
- Conformity with the Directive 2002/95/EC
- MIL-STD 810F/810G (depending on models)

Our creative custom design solutions are proven to meet the demanding, complex needs of some of the toughest industries including the military, aerospace, industrial, oil and gas, electronics, medical and broadcast and telecom fields.



Guardian 1108		LENGTH	WIDTH	DEPTH	LID	BASE	PART NUMBERS
Internal dim	mm	276	200	120	35	85	EMPTY ZG-1108-0301-E-B STANDARD FOAM ZG-1108-0301-F-B CUSTOM INTERIOR ZG-1108-0301-C-B Color: Black Removable Lid
	inch	10 7/8	7 7/8	4 3/4	1 3/8	3 3/8	
External dim	mm	305	270	144			
	inch	12	10 5/8	5 11/16			
Weight Empty	KG 1.62			LBS 3.57			
Weight w/Foam	KG 1.83			LBS 4.03			
Volume	LT 6.6			GAL 1.58			
Buoyancy	KG/MAX 4.2			LBS/MAX 9.25			
Temp. Rating	°C min -33 max +90			°F min -27.4 max +194			
Certifications	IP67 · STANAG 4280 (ed. 2) · DEF STAN 81-41 (lev. J)						



Guardian 1511		LENGTH	WIDTH	DEPTH	LID	BASE	PART NUMBERS
Internal dim	mm	380	270	180	45	135	EMPTY ZG-1511-0502-E-B STANDARD FOAM ZG-1511-0502-F-B CUSTOM INTERIOR ZG-1511-0502-C-B Color: Black
	inch	14 15/16	10 5/8	7 1/16	1 3/4	5 5/16	
External dim	mm	410	340	205			
	inch	16 1/8	13 3/8	8 1/16			
Weight Empty	KG 3.14			LBS 6.92			
Weight w/Foam	KG 3.58			LBS 7.89			
Volume	LT 18.4			GAL 4.75			
Buoyancy	KG/MAX 12.4			LBS/MAX 27.33			
Temp. Rating	°C min -33 max +90			°F min -27.4 max +194			
Certifications	IP67 · STANAG 4280 (ed. 2) · DEF STAN 81-41 (lev. J)						

UNPARALLELED CUSTOMIZED PROTECTION

NEED A CUSTOMIZED PROTECTION SOLUTION?

We Offer In-House Customization and Modification.



Guardian 1714D		LENGTH	WIDTH	DEPTH	LID	BASE	PART NUMBERS
Internal dim	mm	445	345	190	47	143	EMPTY ZG-1714-0602-E-B STANDARD FOAM ZG-1714-0602-F-B CUSTOM INTERIOR ZG-1714-0602-C-B
	inch	17 1/2	13 9/16	7 1/2	1 7/8	5 5/8	
External dim	mm	474	415	214			
	inch	18 11/16	16 5/16	8 7/16			
Weight Empty	KG 4.00			LBS 8.81			
Weight w/Foam	KG 4.70			LBS 10.36			
Volume	LT 29.2			GAL 7.66			
Buoyancy	KG/MAX 19.7			LBS/MAX 43.43			
Temp. Rating	°C min -33 max +90			°F min -27.4 max +194			
Certifications	IP67 - STANAG 4280 (ed. 2) - DEF STAN 81-41 (lev. J)						Color: Black Removable Lid Optional Shoulder Strap Soft Grip Rubber Handle



Guardian 1915		LENGTH	WIDTH	DEPTH	LID	BASE	PART NUMBERS
Internal dim.	mm	480	370	205	50	155	EMPTY ZG-1915-0602-E-B STANDARD FOAM ZG-1915-0602-F-B CUSTOM INTERIOR ZG-1915-0602-C-B
	inch	18 7/8	14 9/16	8 1/16	1 15/16	6 1/8	
External dim	mm	520	435	230			
	inch	20 1/2	17 1/8	9 1/16			
Weight Empty	KG 4,64			LBS 10,22			
Weight w/Foam	KG 5,40			LBS 11,90			
Volume	LT 35.5			GAL 9.24			
Buoyancy	KG/MAX 24,7			LBS/MAX 54,45			
Temp. Rating	°C min -33 max +90			°F min -27,4 max +194			
Certifications	IP67 · STANAG 4280 (ed. 2) · DEF STAN 81-41 (lev. J)						
Color: Black Soft Grip Rubber Handle							



Guardian 2011W		LENGTH	WIDTH	DEPTH	LID	BASE	PART NUMBERS
Internal dim	mm	517	277	217	50	167	EMPTY ZG-2011-0702-E-B-W STANDARD FOAM ZG-2011-0702-F-B-W CUSTOM INTERIOR ZG-2011-0702-C-B-W
	inch	20 3/8	10 7/8	8 9/16	1 15/16	6 9/16	
External dim	mm	546	347	247			
	inch	21 1/2	13 11/16	9 3/4			
Weight Empty	KG 6,00			LBS 13,22			
Weight w/Foam	KG 7,00			LBS 15,43			
Volume	LT 31,0			GAL 8,18			
Buoyancy	KG/MAX 21,5			LBS/MAX 47,39			
Temp. Rating	°C min -33 max +90			°F min -27,4 max +194			
Certifications	IP67 · STANAG 4280 (ed. 2) · DEF STAN 81-41 (lev. J)						Color: Black Removable Lid Soft Grip Rubber Handle Telescoping Handle Wheels with Bearings



Guardian 2116W		LENGTH	WIDTH	DEPTH	LID	BASE	PART NUMBERS
Internal dim	mm	538	405	250	60	190	EMPTY ZG-2116-0802-E-B-W STANDARD FOAM ZG-2116-0802-F-B-W CUSTOM INTERIOR ZG-2116-0802-C-B-W
	inch	21 3/16	15 15/16	9 13/16	2 3/8	7 1/2	
External dim	mm	267	475	292			
	inch	24 11/16	18 11/16	11 1/2			
Weight Empty	KG 10			LBS 22.04			
Weight w/Foam	KG 11.25			LBS 24.80			
Volume	LT 53			GAL 14.00			
Buoyancy	KG/MAX 37.2			LBS/MAX 82.01			
Temp. Rating	°C min -33 max +90			°F min -27.4 max +194			
Certifications	IP67 · STANAG 4280 (ed. 2) · DEF STAN 81-41 (lev. J)						Color: Black Removable Lid Two-Man Side Handles Soft Grip Rubber Handle Telescoping Handle Wheels with Bearings Stainless-Steel Reinforced Padlock Holes



ZEROCASES.COM



Guardian 2317W		LENGTH	WIDTH	DEPTH	LID	BASE	PART NUMBERS
Internal dim	mm	580	440	220	60	160	EMPTY ZG-2317-0602-E-B-W STANDARD FOAM ZG-2317-0602-F-B-W CUSTOM INTERIOR ZG-2317-0602-C-B-W
	inch	22 ^{13/16}	17 ^{5/16}	13	2 ^{3/8}	6 ^{5/16}	
External dim	mm	670	510	372			
	inch	26 ^{3/8}	20 ^{1/16}	10 ^{5/16}			
Weight Empty	KG 9.17			LBS 20.21			Color: Black Two-Man Side Handles Soft Grip Rubber Handle Telescoping Handle Wheels with Bearings
Weight w/Foam	KG 10.40			LBS 22.92			
Volume	LIT 56.10			GAL 14.79			
Buoyancy	KG/MAX 36.70			LBS/MAX 80.90			
Temp. Rating	°C min -33 max +90			°F min -27.4 max +194			
Certifications	IP67 - STANAG 4280 (ed. 2)- DEF STAN 81-41 (lev. J)						



Guardian 2317D		LENGTH	WIDTH	DEPTH	LID	BASE	PART NUMBERS
Internal dim	mm	580	440	330	60	270	EMPTY ZG-2317-1102-E-B-W STANDARD FOAM ZG-2317-1102-F-B-W CUSTOM INTERIOR ZG-2317-1102-C-B-W
	inch	22 ^{13/16}	17 ^{5/16}	13	2 ^{3/8}	10 ^{5/8}	
External dim	mm	670	510	372			
	inch	26 ^{3/8}	20 ^{1/16}	14 ^{5/8}			
Weight Empty	KG 10.54			LBS 23.23			
Weight w/Foam	KG 12.65			LBS 27.88			
Volume	LT 84.2			GAL 22.19			
Buoyancy	KG/MAX 62			LBS/MAX 136.68			
Temp. Rating	°C min -33 max +90			°F min -27.4 max +194			
Certifications	IP67 - STANAG 4280 (ed. 2) - DEF STAN 81-41 (lev. J)						Color: Black Two-Man Side Handles Soft Grip Rubber Handle Telescoping Handle Wheels with Bearings



Guardian 3019		LENGTH	WIDTH	DEPTH	LID	BASE	PART NUMBERS
Internal dim	mm	765	485	305	60	245	EMPTY ZG-3019-1002-E-B-W STANDARD FOAM ZG-3019-1002-F-B-W CUSTOM INTERIOR ZG-3019-1002-C-B-W
	inch	30 1/8	19 1/8	12	2 3/8	9 5/8	
External dim	mm	860	560	355			
	inch	33 7/8	22 1/16	14			
Weight Empty	KG 13.56			LBS 28.89			
Weight w/Foam	KG 16.39			LBS 36.13			
Volume	LT 113.1			GAL 29.85			
Buoyancy	KG/MAX 81.8			LBS/MAX 188.33			Color: Black Two-Man Side Handles Large Front Handle Telescoping Handle Wheels with Bearings
Temp. Rating	°C min -33 max +90			°F min -27.4 max +194			
Certifications	IP67 - STANAG 4280 (ed. 2) - DEF STAN 81-41 (lev. J)						



Guardian 3019D		LENGTH	WIDTH	DEPTH	LID	BASE	PART NUMBERS
Internal dim	mm	765	485	415	60	355	EMPTY ZG-3019-1402-E-B-W STANDARD FOAM ZG-3019-1402-F-B-W CUSTOM INTERIOR ZG-3019-1402-C-B-W
	inch	30 1/8	19 1/8	16 5/16	2 3/8	14	
External dim	mm	860	560	460			
	inch	33 7/8	22 1/16	18 1/5			
Weight Empty	KG 15.02			LBS 33.11			
Weight w/Foam	KG 18.87			LBS 36.13			
Volume	LT 153.9			GAL 40.1			
Buoyancy	KG/MAX 118.5			LBS/MAX 261.24			
Temp. Rating	°C min -33 max +90			°F min -27.4 max +194			
Certifications	IP67 - STANAG 4280 (ed. 2) - DEF STAN 81-41 (lev. J)						Color: Black Two-Man Side Handles Telescoping Handle Wheels with Bearings

FROM PLASTIC TO DEEP DRAWN ALUMINUM TO PRE-ENGINEERED



**DEEP DRAWN HOUSINGS &
VALUE ADDED PROCESSES**



**19" RACKMOUNT
CASES**



**TRANSIT & STORAGE
CONTAINERS**



**CARRY &
INSTRUMENT CASES**

CUSTOM UNIQUE VERSATILE



**ALUMINUM AND
METAL ANODIZING**



**PAINTING &
POWDERCOATING**



**STANDARD AND
CUSTOM ASSEMBLY**



**ALUMINUM
LASER CUTTING**



**CUSTOM
TOOLING**



ROTO MOLDING



**TRUMPF
TRUPUNCH PRESS**



**DEEP DRAWN
ALUMINUM**



**CERTIFIED
WELDING**

©2014 ZERO Manufacturing, Inc. All Rights Reserved. Guardian is a trademark of ZERO Manufacturing, Inc. ZERO reserves the right to modify product specifications, features and information. Technical information is known to be correct at the time of publication.

Call 1.800.500.9376

or email sales@zerocases.com for
engineering & design assistance to meet
specific requirements and customization.



ZERO MANUFACTURING, INC. | 500 West 200 North, North Salt Lake, Utah 84054 USA

Toll Free US 800-500-ZERO (9376) | Direct 801-298-5900 | Fax 801-292-9450 | Email sales@zerocases.com | Web www.zerocases.com

TO LEARN MORE ABOUT ZERO CASES VISIT **WWW.ZEROCASES.COM**